



FLOOR PLAN

Scale 1/4" = 1'-0"

EXTERIOR DOOR SCHEDULE					
NUMBER	DESCRIPTION	LINTEL	LENGTH	+PRESS.	-PRESS.
1	16'-0" X 8'-0" GARAGE DOOR	D	17'-4"	19.48	26.37
2	1 3/4" X 3'-0" X 8'-0" W/ S.L.	BO	6'-8"	20.61	22.71
3	1 3/4" X 3'-0" X 8'-0"	BO	4'-6"	20.82	22.92
4	1 3/4" X 3'-0" X 8'-0"	BO	4'-6"	20.82	29.04
5	1 3/4" X 2'-8" X 8'-0"	BO	4'-4"	20.85	22.95
6	1 3/4" X 2'-4" X 8'-0"	BO	4'-4"	20.85	22.95
7	12'-0" X 8'-0" S.G.D.	B	13'-4"	19.88	21.98
8	5'-0" X 8'-0" S.G.D.	B	6'-6"	20.6	28.59

INTERIOR DOOR SCHEDULE	
NUMBER	DESCRIPTION
9-11	1 3/8" X 2'-8" X 6'-8"
12-13	(2) 1 3/8" X 2'-6" X 6'-8"
14-19	1 3/8" X 2'-6" X 6'-8"
20-21	1 3/8" X 1'-6" X 6'-8"
22	1 3/8" X 2'-6" X 6'-8" POCKET
23-24	6'-0" X 6'-8" BI-FOLD
25	5'-0" X 6'-8" C.O.
26	3'-0" X 6'-8" C.O.
27	2'-6" X 6'-8" C.O.
28	22" X 56" ATTIC STAIR

WINDOW SCHEDULE					
NUMBER	DESCRIPTION	LINTEL	LENGTH	+PRESS.	-PRESS.
1	36 A.S.H. W/ ARCHD TOP	A	5'-10"	20.77	28.95
2	36 A.S.H.	B	5'-10"	20.77	22.87
3	36 A.S.H.	B	5'-10"	20.77	22.87
4	34 A.S.H.	B	5'-10"	20.89	22.99
5	31 A.F.G.	B	5'-10"	21	23.1
6	26 A.S.H.	B	4'-6"	20.88	22.98
7	26 A.S.H.	B	4'-6"	20.88	22.98
8	26 A.S.H.	B	4'-6"	20.88	29.16
9	24 A.S.H.	B	4'-6"	20.96	23.06
10	24 A.S.H. PASS	B	4'-6"	20.96	23.06

ALL DOORS & WINDOWS TO BE INSTALLED OVER P.T. 1 X 4 #2 S.Y.P. BUCKS HEAD & JAMBS: MANUFACTURER'S REQUIRED FASTENERS TO EXTEND THROUGH P.T. BUCKS & A MINIMUM OF 1 1/4" INTO MASONRY.

This structure has been designed to meet or exceed the 110 M.P.H. 3 second gust wind load requirements of the F.B.C. 2001, with 2002 revisions.

IVAN R. DORY
Professional Engineer
229 NORTH JOHN YOUNG PARKWAY
KISSIMMEE, FLORIDA 34741-4983
(407) 847-8765
Fla. Reg. # 13587
Date: _____ PE # 13587

NEW CONCRETE BLOCK RESIDENCE FOR
KENT CUSTOM HOMES, INC.
FOR EDWARDS, OSCEOLA COUNTY, FLORIDA
JON HOKE, 2718 TROPICAL LAKE DR., KISSIMMEE, FL. 34741
PHONE 1-407-847-7742

DRAWN BY
JON HOKE
CHECKED BY
R.L.S.
DRAWING NUMBER
04-021
DATE
5/29/2004
2
OF 5 SHEETS